



XIT

REVISIONS					
SYM	E.O.'S	DESCRIPTION	DRWN	APP'D	DATE

NOTES:

1. IDENTIFY PER HP 8-5 (IMPRESSION STAMP).
2. H.T. TO Rc 36-40 PER HP 1-1
3. BLACK OXIDE PER HP 4-50
4. DIAL READING OF 12" RADIALY ORIENTED TORQUE WRENCH IS 634 TO 720 IN LBS

REDUCED SIZE PRINT

						375x30x3.62		4130 STEEL		MIL-S-6758 COND 3PT		
REQD	PART NO.			REQD	PART NO.			NAME	SIZE	DESCRIPTION	SPECIFICATION	
ASSEMBLY OPP.				ASSEMBLY SHOWN				LIST OF MATERIAL				
				UNLESS OTHERWISE SPECIFIED				DRWN BENEFIEL 8316		<div>WRENCH- 269A6217 NUT</div> <div>HUGHES TOOL COMPANY AIRCRAFT DIVISION CULVER CITY, CALIFORNIA</div> <div>269A 9260</div>		
				DIMENSIONAL TOLERANCES				CHK'D 10-10-68 J-212				
				3 PLACE DECIMAL ± .010				APP'D 10-10-68 J-212				
				2 PLACE DECIMAL ± .03				APP'D 10-10-68 J-212				
				ANGULAR ± 0°30'				APP'D 10-10-68 J-212				
				DIMENSIONS TO BE MET BEFORE PLATING.				APP'D 10-10-68 J-212		<div>269A 9260</div> <div>CODE 02731 SHEET 1 OF 1</div>		
				CORNER RADIUS .062 ON C'				APP'D				
				BORES AND SPOT FACES OF				APP'D				
				1.250 DIA. OR LESS — .093				APP'D				
				RADIUS ON GREATER THAN 1.250 DIA.				APP'D				
NEXT ASSY		USED ON		NEXT ASSY	FINAL ASSY		SCALE FULL					
APPLICATION				QTY REQD								

REF ID: A66666

64-75 PT LBS

WELLING "H" SIZE PUMPS VALV. ETC. E-6

SHOP COPY